



適用機械種類

- 外部受開孔尺寸限制的電控箱
- 改善廠房悶熱局部工作站冷卻應用
- 加工件模具冷卻

APPLICATION

- The external hole size of electrical control panel is limited.
- Cooling for partial workstation
- Cooling for workpiece molding

特性及功能

- 較一般電控箱冷氣風力強。
- 不受特殊電控箱尺寸影響，皆能使用。
- 附萬向輪軸，想吹哪裡都可隨時移動。
- 可調整溫度控制器於一定的溫度範圍內，控制熱源。
- 採用新型高效率環保冷媒，不污染環境。

FEATURE

- The strong wind.
- It's suitable for special dimensions of electrical control panel.
- Attach the caster and can move anywhere.
- Adjust the control board within temperature range and control power source.
- Filling the high-efficiency environmental refrigerant is without pollution.

規格表

CAM SERIES SPECIFICATION

| 型式 Model | | CAM-08S | CAM-12S | CAM-24S |
|---|--------------------------------------|-------------------|-------------|-------------------|
| 冷卻能力 Cooling capacity | BTU/HR 50/60Hz | 6400/8000 | 9600/12000 | 19200/24000 |
| | KCAL/HR 50/60Hz | 1600/2000 | 2400/3000 | 4800/6000 |
| | W 50/60Hz | 1860/2325 | 2790/3488 | 5580/6976 |
| 使用範圍 Operative range | 室溫 Room temperature | 10°C ~ 40°C | | |
| | 箱內溫度 Inside temperature | 15°C ~ 30°C | | |
| 設定範圍 Setting range | 定溫控制 Constant temperature controller | 20°C ~ 40°C | | |
| 電源 Power Source | V | 1ø AC220V 50/60Hz | | 3ø AC220V 50/60Hz |
| 總負荷電流 Total overburdening current consumption | A | 5 | 6 | 8 |
| 外型尺寸 Dimension (DxWxH) | mm | 530x315x986 | 530x315x986 | 689x484x1520 |
| 冷媒 Refrigerant | gas | R134a/R407C | | |
| 總重量 Weight | kg | 53 | 53 | 125 |

CAM-□S

- 智慧型溫度控制 Intelligent temperature control
- 冷卻能力 (x1000 BTU/HR) Cooling capacity
- 工廠專用移動式冷氣機 Moving air conditioner for industries

• 特殊規格設計及其他電壓需求請與我司聯絡。
We welcome customized design and other voltage requirement.
• 本公司因技術需求或升級有隨時更改內容、文字、產品規格之權利，更改部分恕不另行通知。
We reserve the right of changing the specifications and modification without any notice.